	Camera Model	FelyuTech Cable	Capture	Start/ Stop	Playback	Shutter Speed	Aperture Adjustment	ISO Adjustment	Halfway Press	Pull Focus	Digital Zoom	Camera Firmware	Gimble	Roman'k
	RX100 III (RX100M3)	Type-C to Multi	Photo √	Recording Video	√	Adjustment (Via APP)	Adjustment (Via APP)	Adjustment (Via APP)	Halfway Press To Focus	×	Control √	Firmware Version 2.00	Firmware Version Gimbal_V101	Remar k
	RX100 IV (RX100M4) RX100M5A RX100 VI (RX100M6)	Type-C to Multi Type-C to Multi Type-C to Multi	√ √ √	J J	√ √	× × ×	× × ×	× × ×	1	× × ×	1	1. 30 2. 00 1. 00	Gimbal_V101 Gimbal_V101 Gimbal_V101	1. After connecting the cable, be sure to power on the Feiyu St before the camera.
	RX100 VII (RX100M7) ZV-1 DSC-WX500	Type-C to Multi Type-C to Multi Type-C to Multi	<i>y y y y</i>	<i>J J</i>	\ \ \ \	× × ×	× × ×	× × ×	1	× × ×	1	1. 00 1. 0 1. 0	Gimbal_V101 Gimbal_V101 Gimbal_V101	
	DSC-HX90 DSC-RX10 III DSC-RX10 IV	Type-C to Multi Type-C to Multi Type-C to Multi Type-C to Multi	\frac{1}{4}	1	\frac{1}{\sqrt{1}}	× × ×	× × ×	× × ×	1	× × ×	1	1. 0 1. 0 1. 0 2. 00	Gimbal_V101 Gimbal_V101 Gimbal_V101	
														1. Please set the [Ctrl w/ Smartphone] to be off. (Metwork) → [Ctrl w/ Smartphone] → [Off] 2. Set 'USB Commencing' to be "OR Remote': (Metwork) → [PC Remote Function] → [PC Remote] → [On] 3. Set'Still Mig. Save Dest." to be "Camera Only":
	ZV-E10	Type-C to Type-C	√	J	√	×	×	×	×	×	×	1.00	Gimbal_V101	(Network) → [F0 Remote Function] → [Still Img. Save Dest.]: [Cemere Only] 4. Please set [Auto Review] to be "Off" when shooting the time video or Panorams; 5. After connecting the cable, be sure to power on the GAMAX before the camera.
														before the camera. 6. The camera icon on the gimbal screen lights up after a successful comection. And the screen of the camera displays characters 'PC'. 7. When the camera is in photo mode, you can switch between pl
	α 6100 α 6300	Type-C to Multi Type-C to Multi	1	1	√ √	×	×	×	J J	×	1	1.00	Gimbal_V101 Gimbal_V101	the gimbal can only control recording video.
	α 6400 α 6500 α 6600 A 7S	Type-C to Multi Type-C to Multi Type-C to Multi Type-C to Multi	\ \ \ \	J J	\ \ \ \	× × × ×	× × × ×	× × ×	J J	× × × ×	J J	1. 00 2. 00 1. 10 3. 20	Gimbal_V101 Gimbal_V101 Gimbal_V101 Gimbal_V101	
	α 7S II A 7R α 7R II	Type-C to Multi Type-C to Multi Type-C to Multi Type-C to Multi	1	1	\ \ \ \	× × ×	×	× × ×	1	× × ×	1	2.00 2.00 4.00	Gimbal_V101 Gimbal_V101 Gimbal_V101	1.After connecting the cable, be sure to power on the Feiyu : before the camera. 2.Please set [Zoom Setting] to be "ClearImage Zoom" or "Digit
	a 7R III	Type-C to Multi Type-C to Multi Type-C to Type-C	√ √ √	J J	√ √	×	×	×	J J	×	√ √ ×	3. 01 1. 00 1. 00	Gimbal_V101 Gimbal_V101 Gimbal_V101	Zoom 'to emable Digital Zoom. 3.Please set [Auto Review] to be "Off" when shooting the timelapse video or Panorama:
	α 7R M4A α 7 II (A7M2) α 7 III (A7M3)	Type-C to Multi Type-C to Multi Type-C to Multi	√ √ √	J J	√ √	× × ×	×	× × ×	J J	× × ×	J J	1. 00 4. 00 3. 10	Gimbal_V101 Gimbal_V101 Gimbal_V101	
	α9 α9 ΙΙ	Type-C to Multi	1	J	√ √	×	×	×	J	×	1	6. 00 3. 00	Gimbal_V101 Gimbal_V101	1. After connecting the cable, be sure to power on the Feiyu S before the camera.
	A 70	Type-C to Type-C	4	1	√	1	√	4	4	×	×	1. 0	Gimbal_V101	2.Please set the [Otrl w/ Smartphone] to be off. (Network) → [Otrl w/ Smartphone] → [Off] 3.Set 'USB Commencting' to be 'DC Remote': (Network) → [PC Remote Function] → [PC Remote] → [On] 4. Set 'Still Img. Save Dest." to be 'Camera Only': (Network) → [PC Remote Function] → [Still Img. Save Dest.] →
														[Camera Only] 5. Please set [Auto Review] to be "Off" when shooting the timelapse video or Panorama: 1. After connecting the cable, be sure to power on the Feivy S
	a1	Type-C to Multi	4	1	√	×	×	×	4	×	4	1.01	Gimbal_V101	before the camera. 2. Support Optical Zoom when equiped with a Motorize Lens; Ple set [Zoom Setting] to be "GlearImage Zoom" or "Digital Zoom" enable Digital Zoom. 3. Please set [Auto Review] to be "Off" when shooting the
														timelapse video or Panorams: 4.Please set the [Ctrl w/ Smartphone] to be off. (Network) → [Ctrl w/ Smartphone] → [Off]
Sony		Type-C to Multi	√	J	4	×	×	×	J.	×	4	1. 01	Gimbal_V101	1.After connecting the cable, be sure to power on the gimbal before the camera. 2. Support Optical Zoom when equiped with a Motorize Lens; Ple set [Zoom Setting] to be "ClearImage Zoom" or "Digital Zoom" enable Digital Zoom. 3.Please set [Auto Review] to be "Off" when shooting the
														timelapse video or Panorama: A.Please set the [Otrl w / Smartphone] to be off: (Network) → [Otrl w / Smartphone] → [Off]
	a7\$ III													1.Please set the [Otr! w/ Smartphone] to be off; (Metwork) → (Otr! w/ Smartphone) → [Off]; 2. Set 'USB Connecting" to be "PC Remote": (Metwork) → [PC Remote Function] → [PC Remote] → [On]; 3. Set ""Still lmg. Save Dest."" to be ""Camera Only"": (Metwork) → [PC Remote Function] → (Still lmg. Save Dest.]
		Type-C to Type-C	√	1	√	1	√	√	1	×	×	1. 01	Gimbal_V101	[Camera Only] 4. The camera icon on the gimbal screen lights up after a successful connection. And the screen of the camera displays characters "PC". 5. Please set [Auto Review] to be "Off" when shooting the
														timelapse video or Panorama: 6. after swaping from one cable to another, both camera and gin need to be rebooted.
														1. Please set the [Ctrl w/ Smartphone] to be off: (Network) → [Ctrl w/ Smartphone] → [Off] 2. After connecting the cable, be sure to power on the gimbal before the camera. 3. The camera icon on the gimbal screen lights up after a suppressful connection
		Type-C to Multi	✓	4	4	×	×	×	J	×	×	1.00	Gimbal_V101	successful connection. 4 Please set [Zoom Setting] to be "ClearImage Zoom" or "Digit Zoom" to enable Digital Zoom. 5 Please set [Autor Review] to be "Off" when shooting the timelapse video or Panorama; 6 after swaping from one cable to another, both camera and gi
	FX3													need to be rebooted. 1.Please set the [Ctr! m/ Smartphone] to be off:
														(Metwork) → (Ctrl w'.Smartphone) → (Off) 2. Set 'USB Connecting" to be "PC Remote": (Metwork) → [PC Remote Function] → [PC Remote] → [On] 3. Set ""Still img. Save Dest." to be ""Camera Only": (Metwork) → [PC Remote Function] → [Still Img. Save Dest.]- [Camera Only]
		Type-C to Type-C	√	4	4	1	√	√	J	×	×	1.00	Gimbal_V101	4. The camera icon on the gimbal screen lights up after a successful connection. And the screen of the camera displays characters "PC". 5. Please set (Auto Review) to be "Off" when shooting the timelapse video or Panorams; 6. after swaping from one cable to another, both camera and gi
														6.after swaping from one cable to another, both camera and gi need to be rebooted.
		Type-C to Multi	√	J	4	×	×	×	J	×	1	1.00	Gimbal_V101	 After connecting the cable, be sure to power on the gimbal before the camera. Queerate digital zoom, the camera's digital zoom function nee to be turned on.
	A7M4													1. Please set the [Otri w/ Smartphone] to be off: (Metwork) → [Otri w/ Smartphone] → [Off] 2. Set 'USB Commencing' to be 'PC Remote': (Metwork) → [PC Remote Function] → [PC Remote] → [On]Set the
		Type-C to Type-C	4	J	√	4	√	√	1	×	×	1.00	Gimbal_V101	"USB Connection" to be "Computer Remote". The specific settin method is as follows: Step 1: Set the computer remote control the camera. MEMU — network — transmission/remote — Computer remote control function — computer remote control — open 3. Mhen using the electronic focusing function of the camera, need to set the lens mode to AF and camera mode to MF.
														need to set the lens mode to AF and camera mode to MF. 4. Settings to avoid losing photos when taking photos: Network → Transfer/Remote → PC Remote Control → Still Imp Save Dest: → Camera only.
	A7RM IV	Type-C to Multi	4	J	√	×	×	×	×	×	4	1, 10	Gimbal_V103	1. After connecting the cable, be sure to power on the gimbal before the camera. 2. Support Optical Zoom when equiped with a Motorize Lens; Ple set [Zoom Setting] to be "ClearImage Zoom" or "Digital Zoom" enable Digital Zoom.
	FDR-AX60	Type-C to Multi	×	4	√	×	×	×	√	×	√	1.00	Gimbal_V104	emable Digital Zoom. 3. Please set [Auto Review] to be "Off" when shooting the timelapse video or Panorama;
	FDR-AX700	Type-C to Multi	×	, ,	√	×	×	×	, ,	×	4	1.00	Gimbal_V104	
rand	Camera Model	Cable	Capture Photo	Start/ Stop Recording Video	Playback	Shutter Speed Adjustment (Via APP)	Aperture Adjustment (Via APP)	ISO Adjustment (Via APP)	Halfway Press To Focus	Pull Focus	Digital Zoom Control	Camera Firmware Version	Gimble Firmware Version Gimbal V101	Remark
	EOS M50 Mark II EOS M6 Mark II	Type-C to Micro Type-C to Micro Type-C to Type-C	4	1	1	×	×	×	× ×	1	×	1. 1. 0	Gimbal_V101 Gimbal_V101 Gimbal_V101	1. Mhen taking photos or recording video from the gimbal, it is recommended to annually set the camera to the corresponding m otherwise control failure may occur. 2. Switch to NET Mode on the lens when use pull focus. 3. Mhen shooting timelapse video, please set the Canon camera 'hange Review' to be off
	Powershot	Type-C to Type-C	√	J.	4	√	√	√	×	√	×	1. 0. 1	Gimbal_V101	1. Be sure camera Wi-Fi is off before connecting the cable 2. When taking photos or recording video from the gimbal, it i recommended to manually set the camera to the corresponding m otherwise control failure may occur.
	G7 X Mark III E0S 200D II (250D)	Type-C to Type-C	4	√	√	×	×	×	×	√	×	1. 0. 0	Gimbal_V101	otherwise control failure may occur. S. Switch to WEF Mode on the lens when use pull focus. 4. When shooting timelapse video, please set the Canon camera "Image Review" to be off
	EOS 850D EOS 80D EOS 90D	Type-C to Micro Type-C to Mini (Optional) Type-C to Micro	4	J	1	√ × ×	√ × ×	√ × ×	×	1	×	1. 0. 0	Gimbal_V101 Gimbal_V101 Gimbal_V101	 When taking photos or recording video from the gimbal, it i recommended to manually set the camera to the corresponding m otherwise control failure may occur.
	EOS 60 Mark II	Type-C to Micro Type-C to Mini (Optional) Type-C to Mini (Optional)	4	1	√ √	×	×	×	×	1	×	1. 1. 8	Gimbal_V101 Gimbal_V101 Gimbal_V101	otherwise control failure may occur. 2. When using the gimbal to control focus electronically, you need to switch the lens between AF and MF to see which best fyour need. 3. When shooting timelapse video, please set the Canon camera "Image Review" to be off.
	EOS 5D Mark III EOS 5D Mark IV EOS 5DS R	Type-C to Mini (Optional) Type-C to Micro Type-C to Micro	\frac{1}{4}	J J	\frac{1}{\sqrt{1}}	× × √	× × ×	×	× × ×	√ √ ×	× × ×	1. 3. 5 1. 1. 2 1. 1. 1	Gimbal_V101 Gimbal_V101 Gimbal_V101	4. EGS 900/EGS 2000 camera needs to be powered on in photo mo otherwise the camera screen may not display.
Canon	EOS FR EOS RP	Type-C to Micro Type-C to Type-C Type-C to Type-C	4	1	<i>J</i>	×	×	×	× × ×	√ √	×	1. 1. 1	Gimbal_V101 Gimbal_V101 Gimbal_V101	1. Please switch photo / video mode on camera manually. 2. Switch to "ME" Mode on the lens when use pull focus. 3. Please do not use the release cable to control the video recording while in photo mode in BP/RS/R6 camera as it is eas cause the camera crash.
	EOS R	Type-C to Type-C	4	1	√ √	×	×	×	×	1	×	1. 1. 1	Gimbal_V101	cause the camera crash. 4. When shooting timelapse video, please set the Canon camera 'Image Review' to be off 5. It shows that using the adapter with the EF Mount Lens will increase the delay of pull focus. 6. If connect camera to external device via HDMI Cable, need to
	EOS R6	Type-C to Type-C	√	J	√	√	√	√	×	√	×	1.1.1	Gimbal_V101	set the "HDMI Display" to be display both on camera screen an the other device to control capture photo or video recording. 1. After the gimbal and camera are turned on, you need to wait about 10 seconds to establish a connection
	EOS R5C	Type-C to Type-C	4	J	4	4	√	√	×	4	×	1. 0. 0. 1	Gimbal_V1.03	about 10 seconds to establish a connection 2.1men the samera is in photo file, the gimbal can control ta and recording: 3.1men the camera is in video file, the gimbal can control recording 4.1men you look back at an image, you have to switch to photo and when you look back at a video, you have to switch to vide
	EOS R7 EOS R10 EOS R8	Type-C to Type-C Type-C to Type-C Type-C to Type-C	√ √ √	J J	√ √	J J	√ √ √	√ √ √	× × ×	J J	× × ×	1. 0. 1 1. 0. 1 1. 0. 0	Gimbal_V1.04 Gimbal_V1.04 Gimbal_V1.20	and when you look back at a video, you have to switch to vide Please switch photo / video mode on camera manually.
	EOS R50	Type-C to Type-C	4	J	4	4	√	4	×	4	×	1. 0. 0	Gimbal_V1.20	Please switch photo / video mode on camera manually. To pull focus with gimbal, the focus mode toggle on the came should be set to MF. I. Please switch photo / video mode on camera manually.
rand	EOS R6 Mark II Camera Model	Type-C to Type-C Cable	Capture Photo	√ Start/ Stop Recording Video	√ Playback	Shutter Speed Adjustment (Via APP)	Aperture Adjustment (Via APP)	ISO Adjustment (Via APP)	X Halfway Press To Focus	√ Pull Focus	X Digital Zoom Control	1.1.2 Camera Firmware Version	Gimbal_V1.20 Gimble Firmware Version	2. To pull focus with gimbal, the focus mode toggle on the came should be set to MF. Remark
	GH5S	Ture-A · -	√ ·	√ · · · · · · · · · · · · · · · · · · ·	J			(Via APP)	×	√			Gimbal_V101	1. Set the USB Mode to be PC(tether) on camera. 2 Turn off the Camera Mi-Fi before use the cable to control camera as Wi-Fi and USB Trigger can not used at the same time. 3. The camera will auto focus when control capture photo.
		Type-C to Type-C	√ 	· ·	*	×	×	^	*	V	×	1. 2	wa1_V101	4. To pull focus with gimbal, the focus mode toggle on the cam should be set to MF. 5. When the camera is connected to the gimbal, if you open the album and do nothing, the camera may freeze.
		Type-C to DC2.5mm	√	√	J	×	×	×	J	×	×	2. 60	Gimbal_V101	When switched to Photo mode, the camera won't respond to vide capturing commands; when switched to video mode, the camera war respond to photo-capturing commands. 1. Set the USB Mode to be PC(tether) on camera.
	GH5	Type-C to Type-C	4	J	√	×	×	×	×	√	×	2. 60	Gimbal_V101	1. Set the USB Mode to be PC(tether) on camera. 2. Turn off the Camera Wi-Fi before use the cable to control camera as Wi-Fi and USB Trigger can not used at the same time. 3. The camera will suto focus when control capture photo. 4. To pull focus with gimbal, the focus mode toggle on the came should be set to WF. 5. When the camera is connected to the gimbal, if you open the
	GH4 G9	Type-C to DC2.5mm Type-C to DC2.5mm	<i>J</i>	1	J	×	×	×	1	×	×	2. 70	Gimbal_V101 Gimbal_V101	5. When the camera is connected to the gimbal, if you open the album and do nothing, the camera may freeze. Please switch photo / video mode on camera manually.
asonic	69 S5	Type-C to DC2.5mm Type-C to DC2.5mm	√ √	1	√ √	×	×	×	1	×	×	2.00	Gimbal_V101 Gimbal_V101	Please switch photo / video mode on camera manually. 1. Set the USB Mode to be PC(tether) on camera. 2. Turn off the Gamera Ni-Fi before use the cable to control
		Type-C to Type-C	4	V	√	×	×	×	×	1	×	2. 00	Gimbal_V101	2. Turn off the Gamera Wi-Fi before use the cable to control camera as Wi-Fi and USB Trigger can not used at the same time 3. The camera will auto focus when control capture photo. 4. To pull focus with gimbal, the focus mode toggle on the cam should be set to WF.
	GH6	Type-C to DC2.5mm	4	V	J	×	×	×	J	×	×	1. 20	Gimbal_V103	Please switch photo / video mode on camera manually. 1. Set the USB Mode to be PC(tether) on camera. 2. Turn off the Gamera Hi-Fi before use the cable to control
		Type-C to Type-C	4	V	√	×	×	×	×	1	×	1. 20	Gimbal_V103	2. Turn off the Gamera Wi-Fi before use the cable to control camera as Wi-Fi and USB Trigger can not used at the same time 3. The camera will auto focus when control capture photo. 4. To pull focus with gimbal, the focus mode toggle on the cam should be set to WF.
	\$511	Type-C to DC2.5mm	√	4	J	×	×	×	J	×	×	1.00		Please switch photo / video mode on camera manually. 1. Set the USB Mode to be PC(tether) on camera. 2. Turn off the Camera Mi-Fi before use the cable to control camera, as Mi-Fi, and USB Trieser can not used at the same time.
		Type-C to Type-C	4	√	√	× Shutter Speed	× Aperture	×	×	1	×	1.00 Camera	Gimbal_V120	camera as Wi-Fi and USB Trigger can not used at the same time. 3. The camera will auto focus when control capture photo. 4. To pull focus with gimbal, the focus mode toggle on the cam should be set to MF.
	Camera Model	Gable Type-C to Type-C	Capture Photo	Start/ Stop Recording Video	Playback ×	Shutter Speed Adjustment (Via APP)	Adjustment (Via APP)	Adjustment (Via APP)	Halfway Press To Focus	Pull Focus ×	Digital Zoom Control	Firmware Version	Gimble Firmware Version Gimbal_V101	Remark
	Z7 Z5 Z6	Type-C to Type-C Type-C to Type-C Type-C to Type-C Type-C to Type-C	\frac{1}{4}	J J	√ √ √	× × × ×	× × × × ×	× × × × ×	× × × ×	× × × ×	× × × × ×	1. 00 1. 11 2. 00 1. 00	Gimbal_V101 Gimbal_V101 Gimbal_V101 Gimbal_V101	1. After connecting the cable, be sure to power on the Feiyu SDRP before the camera and wait for about 6 seconds fi successfully connection after camera power on 2. Please switch photo / video mode on camera manually.
	Z6 II Z50	Type-C to Type-C Type-C to Micro	√ √	J	J	×	×	×	×	×	×	1.00	Gimbal_V101 Gimbal_V101	1. After connecting the cable, be sure to power on the Felyu gimbal before the camera and wait for about 6 seconds for
	Z fo	Type-C to Type-C	√	J	√	×	×	×	×	√	×	1.10	Gimbal_V101	gimbal before the camera and wait for about 6 seconds for successfully connection after camera power on 2. Please switch photo / video mode on camera manually. 3. To operate digital focusing in video mode, you need to set camera's focusing mode to AF-FS or AF-FC. When operating dig focus in photo mode, the focus mode of the camera cannot be M mode.
			4	√	×	×	×	×	×	√	×	1. 10	Gimbal_V104	successfully connection after camera power on 2. Control the camera with the gimbal, the camera Live View function needs to be enabled 3. Gimbal can control camera recording only when the camera is turned on in video recording mode
	D7500	Type-C to Micro												4. The camera screen does not show the duration of the video, only lights 5. The camera button is unavailable when connected to the gimb 6. When controlling the electronic focus, the lens needs to be AF mode and is slow
	D7500	Type-C to Micro		-	 									1. After connecting the cable, be sure to power on the gimbal before the camera and wait for about 6 seconds to hear the "click" sound for successfully connection after camera power 2 Central the among with the signified the among line View.
	D7500	Type-C to Micro					×	×	×	√	×	1. 2	Gimbal_V104	2. Control the camera with the glabal, the camera Live View function needs to be enabled 3. Glabal can control camera recording only when the camera is turned on in video recording mode 4. If you go back to the album and play the video, you have to reconnect to control it again.
ikon	D7500 D850	Type-C to Micro Type-C to Micro	4	J	1	×						-	1	-
ikon	D850					×								After connecting the cable, be sure to power on the Feiyu gimbal before the camera and wait for about 6 seconds for successfully connection after camera power on
ikon			<i>y</i>	,	<i>y</i>	× ×	×	×	×	4	×	1. 00	Gimbal_V104	gimbal before the camera and wait for about 6 seconds for successfully connection after camera power on 2.Please switch photo / video mode on camera manually. 3.To operate digital focusing in video mode, you need to set camera's focusing mode to AF-FS or AF-FC. When operating dig
ikon	D850	Type−C to Micro					X Aperture Adjustment (Via APP)	X ISO Adjustment (Via APP)	X Halfway Press To Focus	√ Pull Focus	X Digital Zoom	1.00 Camera Firmware Version	Gimbal_V104 Gimble Firmware Version	gimbal before the camera and wait for about 6 seconds for successfully connection after camera power on 2.Please switch photo / video mode on camera manually. 3.To operate digital focusing in video mode, you need to set camera's focusing mode to AF-FS or AF-FC. When operating dig focus in photo mode, the focus mode of the camera cannot be M
i kon	D850 Z30 Camera Model X-T20	Type-C to Micro Type-C to Type-C	√ Capture	, Start/ Stop	V	× Shutter Speed Adjustment	Aperture Adjustment (Via APP)	ISO Adjustment	Halfway Press		Digital Zoom Control	Camera Firmware Version 2.01	Gimble Firmware Version Gimbal_V101	simbal Defore the camera and wait for about 6 seconds for successfully connection after camera power on 2. Pleass switch photo / video mode on camera manually. 3. To operate digital flocusing in video mode, you need to set camera's focusing mode to AF-FS or AF-FC. When operating digit focus in photo mode, the focus mode of the camera cannot be M mode. Remark 1. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [M STITING] menu
rand	230 Camera Model X-120 X-130 X-A5 X-A7	Type-C to Micro Type-C to Type-C Cable Type-C to TRS2.5 Type-C to TRS2.5 Type-C to TRS2.5 Type-C to TRS2.5	Capture Photo	Start/ Stop Recording Video	J J J	× Shutter Speed Adjustment (Via APP) ×	Aperture Adjustment (Via APP) × × ×	ISO Adjustment (Via APP) × × ×	Halfway Press To Focus	Pull Focus X X X	Digital Zoom Control X X X	Camera Firmware Version 2.01 1.00 2.00 1.00	Gimble Firmware Version Gimbal_V101 Gimbal_V101 Gimbal_V101 Gimbal_V101	simbal Defore the camera and sait for about 6 seconds for successfully connection after camera power on 2. Please saitch photo / video mode on camera manually. 3. To operate distillationsuing in video mode, you need to set camera is focusing mode to AF-FS on AF-FO. When operating dig focus in photo mode, the focus mode of the camera cannot be M mode. Remark LPlease sat [MIC/REMOTE RELEASE] to be [REMOTE] under the [M SSTITMS] menuments of the camera manually. The Felyu SC can control camera to start recording.
ikon	Z30 Camera Model X-120 X-130 X-AS	Type-C to Micro Type-C to Type-C Cable Type-C to TRS2.5 Type-C to TRS2.5	Capture Photo	Start/ Stop Recording Video	√ Playback √ √	× Shutter Speed Adjustment (Via APP) × ×	Aperture Adjustment (Via APP) × ×	ISO Adjustment (Via APP) × ×	Halfway Press To Focus J	Pull Focus × ×	Digital Zoom Control	Camera Firmware Version 2.01 1.00	Gimble Firmware Version Gimbat_V101 Gimbat_V101 Gimbat_V101	simbal before the camera and sait for about 6 seconds for successfully connection after camera poper on 2. Please saitch photo / video mode on camera manually. 3. To operate digital focusing in video mode, you need to set camera is focusing mode to AFFS on AFFS. These operating digital in photo mode. The focus mode of the camera cannot be \$\frac{\text{Remark}}{2}\$ and \$\frac{\text{TIMO}}{2}\$ menually. The feature of the camera cannot be \$\frac{\text{Remark}}{2}\$ and \$\frac{\text{TIMO}}{2}\$ menually. The Felyu SC can control camera to start recording. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOV SETTIMO] menually. The Felyu SC can control camera to start recording. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOV SETTIMO] menually. The felyu SC can control camera to start recording.
i kon	230 Camera Model X-120 X-130 X-A5 X-A7 X-1100 X-H1	Type-C to Micro Type-C to Type-C Cable Type-C to TRS2.5	Capture Photo J J J J J J J J	Start/Stop Recording Video	J J J J J J J J J J J J J J J J J J J	× Shutter Speed Adjustment (Via APP) × × × ×	Aperture Adjustment (Via APP) × × × × ×	ISO Adjustment (Via APP)	Halfway Press To Focus J J J J J J	Pull Focus X X X X X	Digital Zoom Control X X X X X	Camera Firmware Version 2.01 1.00 2.00 1.00 2.00 2.01	Gimble Firmware Version Gimbal_V101 Gimbal_V101 Gimbal_V101 Gimbal_V101 Gimbal_V101	simbal Defore the camera and sait for about 6 seconds for successfully connection after camera power on 2. Please smitch photo / video mode on camera manually. 3. To operate distint focusing in video mode, you need to set camera's focusing mode to AFFS on AFFG. When operating dig focus in photo mode, the focus mode of the camera cannot be 8 mode. Remark Remark L.Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MIC/REMOTE] menu 2.2. After switch to video mode on camera manually. The Felyu SC can control camera to start recording. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOV SETTINO] menu 3. Make sure to connect Felyu SODP to the camera 2.5 mm port. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOV SETTINO] menu
ikon	230 Camera Model X-120 X-130 X-45 X-47 X-1100 X-11 X-13	Type-C to Micro Type-C to Type-C Cable Type-C to TRS2.5	Capture Photo J J J J J J J J J J J J J	Start/ Stop Recording Video	J J J J J J J J J J J J J J J J J J J	X Shutter Speed Adjustment (Via APP) X X X X X	Aperture Adjustment (Via APP)	ISO Adjustment (Via APP)	Halfway Press To Focus J J J J J J J J J J J J J J J J J J	Pull Focus X X X X X X X	Digital Zoom Control X X X X X X X	Camera Firmare Version 2.01 1.00 2.00 1.00 2.00 2.01 3.01	Gimble Firmware Version Gimbal_V101 Gimbal_V101 Gimbal_V101 Gimbal_V101 Gimbal_V101 Gimbal_V101 Gimbal_V101 Gimbal_V101	simbal before the camera and sait for about 6 seconds for successful y connection after camera power on 2. Please saitch photo / video mode on camera manually. 3. To operate distul focusing in video mode, you need to set camera's focusing mode to AF-FS or AF-FD. When operating districus in photo mode, the focus mode of the camera cannot be M mode. Remark Remark 1. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [M SETIING] menu 2. After switch to video mode on camera manually. The Felyu SC can control camera to start recording. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOV SETIING] menu 1. Mode sure to connect Felyu SCORP to the camera sq.2.5mm port. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOV SETIING] menu
rand	Z30 Camera Mode I X-T20 X-A5 X-A7 X-T100 X-H1 X-T3 X-T4 X-T4 X-T200 X-E3	Type-C to Micro Type-C to Type-C Cable Type-C to TRS2.5	Capture Photo J J J J J J J J J J J J J	Start/Stop Recording Video J X X J J J	Playback J J J J J J J J J J J J J	Shutter Speed Adjustment (Via APP) × × × × × × × × × × ×	Aperture Adjustment (Via APP) X X X X X X X X X	ISO Adjustment (Via APP)	Halfway Press To Focus J J J J J J J J J J J J J	Pull Focus X X X X X X X X X X	Digital Zoom Control X X X X X X X X X	Camera Firmware Version 2.01 1.00 2.00 1.00 2.01 3.01 1.00 1.00 1.02 1.00 1.22	Gimble Firmware Version Gimbal_VI01	simbal before the camera and sait for about 6 seconds for successfully connection after camera power on 2. Please saitch photo / video mode on camera manually. 2. Please so sitch photo / video mode on camera manually. 3. To operate digital flocusing in video mode, you need to set camera is flocusing mode to AFFS on AFFC. When operating digit flocus in photo mode. The flocus mode of the camera cannot be 8 mode. Remark Remark 1. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Camera cannot be 18 mode. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Camera to start recording. 1. Make sure to connect Feijus SODP to the camera a2.5 mm port. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Camera manually. 1. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Camera manually. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Camera manually. 1. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Camera manually. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Sectific operations: Enter the setting interface setting interface the camera setting interface setting interfac
likon	Camera Model X-120 X-130 X-A5 X-A7 X-1100 X-H1 X-T3 X-T4 X-510 X-7200	Type-C to Micro Type-C to Type-C Cable Type-C to TRS2.5 Type-C to TRS3.5 (Optional) Type-C to TRS3.5 (Optional)	Capture Photo J J J J J J J J J J J J J	Start/ Stop Recording Video J X X J J J J	J Playback J J J J J J J J J J J J J	Shutter Speed Adjustment (Via APP) × × × × × × × ×	Aperture Adjustment (Via APP)	ISO Adjustment (Via APP)	Halfway Press To Focus J J J J J J J J J J J J J J J J J J	Pull Fecus X X X X X X X X X	Digital Zoom Control X X X X X X X X	Canera Firmsare Version 2.01 1.00 2.00 1.00 2.01 3.01 1.00 1.00 1.00	Gimble Firmware Version Gimbal_V101	simbal before the camera and sait for about 6 seconds for successfully connection after camera power on 2. Please saitch photo / video mode on camera manually. 2. Please so sitch photo / video mode on camera manually. 3. To operate digital flocusing in video mode, you need to set camera is flocusing mode to AFFS on AFFC. When operating digit flocus in photo mode. The flocus mode of the camera cannot be 8 mode. Remark Remark 1. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Camera cannot be 18 mode. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Camera to start recording. 1. Make sure to connect Feijus SODP to the camera a2.5 mm port. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Camera manually. 1. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Camera manually. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Camera manually. 1. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Camera manually. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTETHING] menu Sectific operations: Enter the setting interface setting interface the camera setting interface setting interfac
rand	Z30 Camera Mode I X-T20 X-A5 X-A7 X-T100 X-H1 X-T3 X-T4 X-T4 X-T200 X-E3	Type-C to Micro Type-C to Type-C Cable Type-C to TRS2.5	Capture Photo J J J J J J J J J J J J J	Start/ Stop Recording Video J X X J J J J	J Playback J J J J J J J J J J J J J	Shutter Speed Adjustment (Via APP) × × × × × × × × × × ×	Aperture Adjustment (Via APP) X X X X X X X X X	ISO Adjustment (Via APP)	Halfway Press To Focus J J J J J J J J J J J J J	Pull Focus X X X X X X X X X X	Digital Zoom Control X X X X X X X X X	Camera Firmware Version 2.01 1.00 2.00 1.00 2.01 3.01 1.00 1.00 1.02 1.00 1.22	Gimble Firmware Version Gimbal_V101	simbal Defore the camera and sait for about 6 seconds for successfully connection after camera poper on 2. Please saitch photo / video mode on camera manually. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTE STITINO] menu 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTE STITINO] menu 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTE STITINO] menu 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTE STITINO] menu 3. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTE STITINO] menu 4. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTE STITINO] menu 5. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTE STITINO] menu 5. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTE STITINO] menu 6. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTE STITINO] menu 6. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTE STITINO] menu 6. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTE STITINO] menu 6. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTE STITINO] menu 6. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOTE STITINO] menu Societic operations: Enter the setting interfaction of the setting interfacti
dikon dirand	Z30 Camera Model X-T20 X-T30 X-A5 X-A7 X-T100 X-H1 X-T3 X-T4 X-S10 X-T200 X-E3	Type-C to Micro Type-C to Type-C Cable Type-C to TRS2.5	Capture Photo J J J J J J J J J J J J J	Start/ Stop Recording Video V X X J J J J	Playback J J J J J J J J J J J J J	Shutter Speed Adjustment (Via APP) × × × × × × × × × × × × ×	Aperture Adjustment (Via APP)	ISO Adjustment (Via APP)	Halfuny Press To Focus J J J J J J J J J J J J J	Pull Focus X X X X X X X X X X X	Digital Zoom Control X X X X X X X X X	Camera Firmware Version 2.01 1.00 2.00 1.00 2.01 3.01 1.00 1.02 1.00 1.00 1.00	Gimbal VIOI Gimbal_VIOI	simbal before the camera and sait for about 6 seconds for successfully connection after camera poper on 2. Please saitch photo / video mode on camera manually. 2. Please saitch photo / video mode on camera manually. 3. To operate digital focusing in video mode, you need to set camera is focusing mode to AFFS on AFFC. When operating digitation is photo mode, the focus mode of the camera cannot be 8 mode. Remark 1. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MICREMOTE] menu 2. After switch to video mode on camera manually. The Felyu SC cam control camera to start recording. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MICREMOTE] menu 1. Make sure to connect Felyu SCOMP to the camera ac 2.5mm port. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MICREMOTE] menu 1. Make sure to connect Felyu SCOMP to the camera ac 2.5mm port. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MICREMOTE] menu 1. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MICREMOTE] menu Schiller menu
irand	Z30 Camera Model X-120 X-130 X-A5 X-A7 X-1100 X-H1 X-13 X-14 X-510 X-1200 X-E3 X-1200 X-E3 X-1200 X-H2 X-H2 X-H2	Type-C to Micro Type-C to Type-C Cable Type-C to TRS2.5	Capture Photo J J J J J J J J J J J J J J J J J J	Start/Stop Recording Video X X X J J J J J J J J J	Playback J J J J J J J J J J J J J J J J J J	X Shutter Speed Adjustment (Via APP) X X X X X X X X X X X X X	Aperture Adjustment (Via APP)	ISO Adjustment (Via APP)	Halfuny Press To Focus J J J J J J J J J J J J J	Pull Focus X X X X X X X X X X X X X	Digital Zoom Control X X X X X X X X X X X X X	Camera Firmware Version 2.01 1.00 2.00 1.00 2.01 3.01 1.00 1.02 1.00 1.22 1.00 1.22	Gimbal_V101 Gimbal_V103	simbal before the camera and wait for about 6 seconds for successfully connection after camera power on 2. Please switch photo / video mode on camera manually. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 3. Make sure to connect Feilyu SCORP to the camera a2.5cm port. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 3. Make sure to connect Feilyu SCORP to the camera a2.5cm port. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 3. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 4. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 5. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 5. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 5. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 5. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu Specific operations: Enter the setting interface video Settings Microphone/Remote shutter Settings/remote con 2. Please switch photo/ video mode on camera manually.
and	Z30 Camera Model X-T20 X-T30 X-A5 X-A7 X-T100 X-H1 X-T3 X-T4 X-T30 X-T200 X-E3 X-T30 11 X100V	Type-C to Micro Type-C to Type-C Cable Type-C to TRS2.5	Copture Photo J J J J J J J J J J J J J	Start/ Stop Recording Video J X X J J J J J J J J J J	Playback J J J J J J J J J J J J J J J J J J	X Shutter Speed Adjustment (Via APP) X X X X X X X X X X X X X	Aperture Adjustment (Via APP)	ISO Adjustment (Via APP)	Halfway Press To Focus J J J J J J J J J J J J J	Pull Focus X X X X X X X X X X X X X	Digital Zoom Control X X X X X X X X X X X X X	Camera Firmware Version 2.01 1.00 2.00 1.00 2.01 3.01 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00	Gimbal_V101 Gimbal_V103	simbal before the camera and wait for about 6 seconds for successfully connection after camera power on 2. Please switch photo / video mode on camera manually. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 3. Make sure to connect Feilyu SOORP to the camera a2.5 mm port. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 3. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 4. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 5. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 5. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 6. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 6. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 6. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 6. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 6. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 6. SETTINNO] menu 6. SETTINNO] menu 6. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 6. SETTINNO] menu 6. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 6. SETTINNO] menu 6. SETTINNO] menu 7. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 7. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVERTINNO] menu 8. SETTINNO] menu 8. SETTINNO] menu 8. SETINNO]
rand	230 Camera Model X-720 X-730 X-A5 X-A7 X-1100 X-H1 X-73 X-T4 X-510 X-720 X-E3 X-T30 II X100V GFX 100S X-H2S X-H2 X-T5	Type-C to Micro Cable Type-C to Type-C Cable Type-C to TRS2.5 Type-C to TRS2.5	Capture Photo J J J J J J J J J J J J J J Capture	Start/ Stop Recording Video J X X J J J J Start/ Stop Recording Video	Playback J J J J J J J J J J J J J	Shutter Speed Adjustment (Via APP) X X X X X X X X X X X X X	Aperture Adjustment (Via APP)	ISO Adjustment (Via APP)	Halfway Press To Focus J J J J J J J J J Halfway Press	Pull Focus X X X X X X X X X X X X X	Digital Zoom Control X X X X X X X X X X Digital Zoom Control	Camera Firmare Version 2.01 1.00 2.00 1.00 2.01 3.01 1.00 1.02 1.00 1.22 1.00 1.22 1.00 1.22 1.00 1.22 1.00 1.22 1.00 1.22 1.00 1.22 1.00 1.22 1.00 1.22	Firmware Version Gimbal_V101 Gimbal_V102 Gimbal_V103	simbal before the camera and mait for about 6 seconds for successfully connection after camera power on 2. Please switch photo / video mode on camera manually. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 3. After switch to video mode on camera manually. The Felyu SO can control camera to start recording. 1. Make sure to connect Felyu SOMP to the camera 2. Sem port. 2. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 3. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 4. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 5. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 6. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 6. Please switch photo/ video mode on camera manually. 1. Please switch photo/ video mode on camera manually. 1. Please set [MIC/REMOTE RELEASE] to be [REMOTE] under the [MOVETTINO] menu 6. SETTINO] menu 6. SETTINO] menu 7. Please switch photo/ video mode on camera manually. 8. SETTINO] menu Specific operations: Enter the setting interface video Settings Microphone/Remote shutter Settings/remote con 2. Please switch photo/ video mode on camera manually. 9. Please switch photo/ video mode on camera manually. 9. Please switch photo/ video mode on camera manually. 9. Please switch photo/ video mode on camera manually. 9. Please switch photo/ video mode on camera manually. 9. Please switch photo/ video mode on camera manually.