



FY-G4 Handheld Gimbal Firmware V1.21

Update Explanation

Firmware Update Explanation

V1.21 2016.2.4

1. Add function: support for 2.4G wireless remote control which designed by feiyu tech.
2. Optimization the performance of panning following.
3. Some other adjustment.

V1.13 2015.5.8

1. Support to do level calibration by G4 remote control.
 - a. Press the function button on the RC for six times in succession, then gimbal will enter the level calibration mode. The pitching angle can be calibrate by the UP and DOWN button, the roll angle can be calibrate by the LEFT and RIGHT button.
 - b. After finish the level calibration, single press the function button on the RC, the gimbal will exit the level calibration mode and enter the standby mode and save the parameters automatically. Single press the function button on the RC again the gimbal will be awoken immediately.
2. Support to configure the heading following speed mode by G4 remote control.
 - a. Hold the RIGHT button and four press the function button in succession at the same time, the gimbal will accelerate the heading following speed.
 - b. Hold the LEFT button and four press the function button in succession at the same time, the gimbal will slow down the heading following speed.
 - c. There are three heading following speed modes for optional: "SLOW" mode, "NORMAL" mode , "FAST" mode. Default setting is "NORMAL" mode.
 - d. When success configure the heading following speed mode the gimbal will enter the standby mode and save the parameters automatically. Single press the function button on the RC again the gimbal will be awoken immediately.
3. Add a new function: Four press the function button during any working mode, the gimbal will reset to the state of starting up: the pitching and roll angle will turn to the starting angle, and switch to the heading follow mode automatically.
4. Added a status indication of the initialization : In 5 sencond after turning on the gimbal, the LED of the function button will keep fast flashing if the intialization success.

V1.11 2015.1.30

1. Support to connecting by remote control for FY-G4 gimbal.
2. Add a new function: the pitching can be adjust by hand pulling.
3. Add a standby mode: press function button for 3 seconds during working, the gimbal will switch to the standby mode and the motor stop working. Single press the function button, the gimbal will be awoken immediately.

4. Some other internal adjustment.

FEIYU TECH